

Restoration and Lake Management Program for Lake Oscawana

Presented to: LOCA

Stephen Axinn, President – Lake Oscawana Civic Association Dr. Fred Lubnow – Princeton Hydro

August 17, 2008

Agenda

- Toward a Lake Restoration and Management Plan
- Comprehensive Restoration and Management Plan
- NYS DEC TMDL for Phosphorus
- Development of the Management Plan
- Summary of Long-Term Lake and Watershed Conditions
- Recommended Strategy and Funding Plan
 - In-Lake Nutrient Load
 - Vegetation Management
 - Watershed Management
 - Program Management
 - Lake Management Estimated Cost Summary

Toward a Restoration and Lake Management Program

- Since 2002, LO has been considered "impaired" by NYS (under the Federal Clean Water Act)
 - Requiring a Total Maximum Daily Load (TMDL) computation for Phosphorus
 - This TMDL was completed by NYS EPA in 2008.
- Conditions have steadily deteriorated in terms of water quality, in lake-vegetation, E. coli and fecal coliform contamination and other factors that adversely affect the market value of properties with lakerights.
- For over 20 years the Town has conducted weed harvesting operations, but conditions have not improved
- These conditions had long been recognized by the Town's limnologist
- Although the Town of Putnam Valley has a long history of annual monitoring data on LO, LOCA believed that an analysis of such data with a recommended management plan -- focused on a set of action steps -- was needed to address a number of years of decline in the water quality at the Lake.
- In early 2007, Lake Oscawana Civic Association (LOCA) defined the need for development of a comprehensive lake management plan.

Comprehensive Restoration and Management Plan

- The LOCA Board of Directors initiated a formal RFP process with area limnologists to engage one for creation of a Lake Management Plan
- LOCA hired Princeton Hydro, based upon its reputation performing similar studies and its engagement in various lake restoration programs in Putnam County as well as other NY, NJ and PA lakes.
- The idea of comprehensive implies that the management plan needs to consider actions across various areas including:
 - Nutrient Loads
 - Vegetation Conditions
 - Watershed (septic and stormwater runoff)
- The funding for creation of the Lake Management Plan has come from individual contributions by LO residents
 - Various fund raising efforts over the last 12-16 months have collected most of the cost of the Plan
 - Note: We still have a shortfall relative to the cost of the Plan contributions welcome

Comprehensive Restoration and Management Plan

- Lake Oscawana is a vital part of the Town's tax base.
 - Property Owners with Lake Rights represent 14.4 % of the total assessed value by right to LO

Lake Oscawana homeowners and property owners stand to loose tremendous value in their real-estate investments and quality of recreational activities if the Lake conditions go unaddressed.

NYS DEC TMDL for Phosphorus

- In June, 2008 NYS DEC completed its Total Maximum Daily Load (TMDL) computation
- A TMDL addresses ONLY watershed contribution---it does not address inlake phosphate contamination.
- The TMDL recommends an approx 10% reduction in P-load from current levels – focused on Septic Systems and Stormwater Management
- It also recommended formation of a Septic Control District

Table 6. Total Annual Phosphorus Load Allocations for Lake Oscawana¹

	Total Pl	% Reduction		
Source	Current	Allocated	Reduction	% Reduction
Agriculture	7	6	1	9%
Developed Land (non-regulated MS4 stormwater)	49	44	5	10%
Septic Systems	313	284	29	9%
Forest, Wetland, Stream Bank, and Natural Background	141	141	0	0%
LOAD ALLOCATION	509	475	34	7%
Point Sources	0	0	0	0%
Developed Land (regulated MS4 stormwater)	153	125	28	18%
WASTELOAD ALLOCATION	153	125	28	18%
LA + WLA	663	600	62	9%
Margin of Safety	MOS	of 10% built	into the TMD	L endpoint
TOTAL	663	600	62	9%

Development of the Management Plan

- Dr. Fred Lubnow -- Director of Aquatic Programs at Princeton Hydro manages PH's lake restoration and management projects -- has led the creation of the LO Management Plan
- Princeton Hydro utilized annual measurement data collected over a 20 year period by the Town's Limnologist (Dr. George Knocklein) as well as special studies (by Dr. Ken Wagner and Dr. Robert Kortmann) The draft plan has been presented to the Town's Advisory Committee [and approved in principal].
- Public meetings were held and widely attended at which Dr. Fred Lubnow reported to the public. These meetings were televised on Channel 20 and the Town's website.

Summary of Long-Term Lake and Watershed Conditions

- Internal loading accounts for slightly over half of the annual phosphorus load of Lake Oscawana.
- Stormwater and septic systems account for the majority of the external phosphorus load. Lawn and garden fertilizer accounts for much of the remainder.
- Stream #4 (sub-watershed 1)
 generates the largest TP loads
 and is one of the high priority
 locations for watershed
 management.
- Recommendations of the Management Plan are consistent with those of the TMDL.

Annual Phosphorus Budget for Lake Oscawana

Sources of Pollutions	Kilograms	Pounds	Percent Contribution
Surface Runoff	194.1	428.0	19.7
Internal Loading 565.7 Septic Leachate 184.7		1,247.4	57.5
		407.3	18.8
Atmospheric	40.0	88.2	4.1
Total	984,5	2,170.8	100.0

Recommended Strategy and Funding Plan

- Focus areas:
 - IN-LAKE NUTRIENT LOAD
 - Alum P-Inactivation
 - Artificial Circulation
 - Selective Dredging Feasibility
 - VEGETATION MANAGEMENT
 - Mechanical Harvesting
 - WATERSHED MANAGEMENT
 - Stormwater
 - Biofilter
 - Septic Management
 - PROGRAM MANAGEMENT

In-Lake Nutrient Load

		Proposed Timeline						1.
		2008	2009	2010	2011	2012	2013	5-Year Tota
	Estimated Costs							
Management Action	(in 2008 Dollars)	- 1			1 1			
IN-LAKE NUTRIENT LOAD								
Alum P-Inactivation								
Sampling, bench tests, permitting	\$50,000.00		\$50,000					\$50,000
Implementation Costs	\$200,000.00			\$200,000				\$200,000
Operating Costs (post-monitoring)	additional water quality monitoring costs			\$1,000	\$1,000	\$1,000	\$1,000	\$4,000
Metric	Surface / bottom water TP concentration	ons, chlorop	hyll a concer	trations and	Secchi disk	water clarity		
Artificial Circulation								
Design of System Costs	approx. \$10,000.00	\neg			\$10,000		**********	\$10,000
Implementation Costs*	\$190,000.00				\$190,000			\$190,000
Operating Costs (per month of operation Elec. / Maint.)	\$2,600 / month				\$15,600	\$15,600	\$15,600	\$46,800
* does not include any purchase of land, if required								
Metric	Oxic conditions (diss	olved oxyge	n > 1 mg/L) ir	the bottom	waters			
Selective Dredging Feasibility Analysis								
Conduct Bathymetric Survey / Generate Maps and Plan	approx. \$10,000.00			\$7,800				\$7,800
Collect Sediment Samples form three sites				\$7,200				\$7,200
Metric	Quantification and Qualification of Sediments							

Vegetation Management

	Lake Oscawana - Restoration	Progr	am					
		Proposed Timeline						
		2008	2009	2010	2011	2012	2013	5-Year Total
Management Action	Estimated Costs (in 2008 Dollars)							
VEGETATION MANAGEMENT								
Mechanical Harvesting								<u> </u>
New mechanical weed harvester	approx. \$90,000.00		\$90,000					\$90,000
Annual operating costs	approx. \$25,000.00		\$25,000	\$25,000	\$25,000	\$25,000	\$25,000	\$125,000
Metric	Acres harves	ted and aq	uatic plant	biomass			l	

Watershed Management

WATERSHED MANAGEMENT				VI		***	S	
Stormwater								
Retrofitting of approx. 15 catch basins along West Shore Drive	\$90,000.00			\$45,000	\$45,000			\$90,000
Retrofitting of approx. 25-30 catch basins in northeast section	\$150,000.00				\$75,000	\$75,000		\$150,000
Installation of large BMP adjacent to Northview Beach	\$250,000.00						\$250,000	\$250,000
* assume maintenance by Highway Department								
Metric	Stormwater TP and T	SS concent	rations and ca	l culated load	s removed		4	
Biofilter					_		-	
New Lee Ave. Biofilter (planting, stabilization, possible retrofits)								
Initial cost to cleanup and some select plantings	approx. \$5,000.00		\$5,000					\$5,000
Design and implementation of biofilter project	Costs uncertain			?	?			
Metric	Stormwater TP and TSS concentrations and calculated loads removed							
Septic Management			h	-				
Formation of Septic Management District (including ordinances)	no initial costs	N/A	N/A	1				
Development of GIS-based database on septic zone of								
influence and watershed constraints**	approx. \$8,000.00			\$8,000				\$8,000
** does not include costs to compiling and digitizing								
paper database on existing septic systems								
Metric	Development of district and establishment	of regulator	y goals; waters	L shed-based G	I IS database	on septic s	ystems	

Program Management

PROGRAM MANAGEMENT							
Retainer for Limnologist to advise Town and Monitor Program	approx. \$8,500.00	\$8,500	\$8,500	\$8,500	\$8,500	\$8,500	\$42,500
Progress - consulting correspondence, public meetings.							
seeking and applying for grants and other sources of funding							
seeming and applying to grants and outer acardes or raining							-

Lake Management – Estimated Cost Summary

	Lake Oscawana - Restora	ation Prog	gram .					
		Proposed Timeline						
		2008	2009	2010	2011	2012	2013	5-Year Total
	Estimated Costs							
Management Action	(in 2008 Dollars)							
IN-LAKE NUTRIENT LOAD		SO	\$50.000	\$216,000	\$216,600	\$16,600	\$16,600	\$515,800
VEGETATION MANAGEMENT		\$0	\$115,000	\$25,000	\$25,000	\$25.000	\$25.000	\$215,000
WATERSHED MANAGEMENT		\$0	\$5,000	\$53,000	\$120,000	\$75.000	\$250.000	\$503,000
PROGRAM MANAGEMENT		\$0	\$8,500	\$8,500	\$8,500	\$8,500	\$8,500	\$42,500
TOTALS - Annual and Grand		\$0	\$178,500	\$302,500	\$370,100	\$125,100	\$300,100	\$1,276,300

Appendix

